


String manipulation with stringr : : CHEAT SHEET



The **stringr** package provides a set of internally consistent tools for working with character strings, i.e. sequences of characters surrounded by quotation marks.

Detect Matches

str_detect(string, **pattern**) Detect the presence of a pattern match in a string. `str_detect(fruit, "a")`

str_which(string, **pattern**) Find the indexes of strings that contain a pattern match. `str_which(fruit, "a")`

str_count(string, **pattern**) Count the number of matches in a string. `str_count(fruit, "a")`

str_locate(string, **pattern**) Locate the positions of pattern matches in a string. Also **str_locate_all**. `str_locate(fruit, "a")`

Subset Strings

str_sub(string, start = 1L, end = -1L) Extract substrings from a character vector. `str_sub(fruit, 1, 3); str_sub(fruit, -2)`

str_subset(string, **pattern**) Return only the strings that contain a pattern match. `str_subset(fruit, "b")`

str_extract(string, **pattern**) Return the first pattern match found in each string, as a vector. Also **str_extract_all** to return every pattern match. `str_extract(fruit, "[aeiou]")`

str_match(string, **pattern**) Return the first pattern match found in each string, as a matrix with a column for each () group in pattern. Also **str_match_all**. `str_match(sentences, "(a|the) ([^]+)")`

Manage Lengths

str_length(string) The width of strings (i.e. number of code points, which generally equals the number of characters). `str_length(fruit)`

str_pad(string, width, side = c("left", "right", "both"), pad = " ") Pad strings to constant width. `str_pad(fruit, 17)`

str_trunc(string, width, side = c("right", "left", "center"), ellipsis = "...") Truncate the width of strings, replacing content with ellipsis. `str_trunc(fruit, 3)`

str_trim(string, side = c("both", "left", "right")) Trim whitespace from the start and/or end of a string. `str_trim(fruit)`

Mutate Strings

str_sub() <- value. Replace substrings by identifying the substrings with `str_sub()` and assigning into the results. `str_sub(fruit, 1, 3) <- "str"`

str_replace(string, **pattern**, replacement) Replace the first matched pattern in each string. `str_replace(fruit, "a", "-")`

str_replace_all(string, **pattern**, replacement) Replace all matched patterns in each string. `str_replace_all(fruit, "a", "-")`

str_to_lower(string, locale = "en")¹ Convert strings to lower case. `str_to_lower(sentences)`

str_to_upper(string, locale = "en")¹ Convert strings to upper case. `str_to_upper(sentences)`

str_to_title(string, locale = "en")¹ Convert strings to title case. `str_to_title(sentences)`

Join and Split

str_c(..., sep = "", collapse = NULL) Join multiple strings into a single string. `str_c(letters, LETTERS)`

str_c(..., sep = "", collapse = NULL) Collapse a vector of strings into a single string. `str_c(letters, collapse = "")`

str_dup(string, times) Repeat strings times times. `str_dup(fruit, times = 2)`

str_split_fixed(string, **pattern**, n) Split a vector of strings into a matrix of substrings (splitting at occurrences of a pattern match). Also **str_split** to return a list of substrings. `str_split_fixed(fruit, " ", n=2)`

str_glue(..., .sep = "", .envir = parent.frame()) Create a string from strings and {expressions} to evaluate. `str_glue("Pi is {pi}")`

str_glue_data(.x, ..., .sep = "", .envir = parent.frame(), .na = "NA") Use a data frame, list, or environment to create a string from strings and {expressions} to evaluate. `str_glue_data(mtcars, "{rownames(mtcars)} has {hp} hp")`

Order Strings

str_order(x, decreasing = FALSE, na_last = TRUE, locale = "en", numeric = FALSE, ...) ¹ Return the vector of indexes that sorts a character vector. `x[str_order(x)]`

str_sort(x, decreasing = FALSE, na_last = TRUE, locale = "en", numeric = FALSE, ...) ¹ Sort a character vector. `str_sort(x)`

Helpers


str_conv(string, encoding) Override the encoding of a string. `str_conv(fruit, "ISO-8859-1")`

str_view(string, **pattern**, match = NA) View HTML rendering of first regex match in each string. `str_view(fruit, "[aeiou]")`

str_view_all(string, **pattern**, match = NA) View HTML rendering of all regex matches. `str_view_all(fruit, "[aeiou]")`

str_wrap(string, width = 80, indent = 0, exdent = 0) Wrap strings into nicely formatted paragraphs. `str_wrap(sentences, 20)`

¹ See bit.ly/ISO639-1 for a complete list of locales.



Need to Know

Pattern arguments in stringr are interpreted as regular expressions *after any special characters have been parsed*.

In R, you write regular expressions as *strings*, sequences of characters surrounded by quotes ("" or single quotes(')).

Some characters cannot be represented directly in an R string. These must be represented as **special characters**, sequences of characters that have a specific meaning, e.g.

Special Character	Represents
\\	\
\"	"
\\n	new line

Run `?""` to see a complete list

Because of this, whenever a \ appears in a regular expression, you must write it as \\ in the string that represents the regular expression.

Use `writeLines()` to see how R views your string after all special characters have been parsed.

```
writeLines("\\.")
# \.
```

```
writeLines("\\ is a backslash")
# \ is a backslash
```

INTERPRETATION

Patterns in stringr are interpreted as regexes To change this default, wrap the pattern in one of:

regex() (pattern, ignore_case = FALSE, multiline = FALSE, comments = FALSE, dotall = FALSE, ...) Modifies a regex to ignore cases, match end of lines as well of end of strings, allow R comments within regex's, and/or to have . match everything including \n. `str_detect("I", regex("i", TRUE))`

fixed() Matches raw bytes but will miss some characters that can be represented in multiple ways (fast). `str_detect("\u0130", fixed("i"))`

coll() Matches raw bytes and will use locale specific collation rules to recognize characters that can be represented in multiple ways (slow). `str_detect("\u0130", coll("i", TRUE, locale = "tr"))`

boundary() Matches boundaries between characters, line_breaks, sentences, or words. `str_split(sentences, boundary("word"))`

Regular Expressions - Regular expressions, or *regexps*, are a concise language for describing patterns in strings.

MATCH CHARACTERS

```
see <- function(rx) str_view_all("abc ABC 123\t.!\?\\()\}n", rx)
```

string (type this)	regex (to mean this)	matches (which matches this)	example
	a (etc.)	a (etc.)	<code>see("a")</code>
\\.	\\.	.	<code>see("\\.")</code>
\\!	\\!	!	<code>see("\\!")</code>
\\?	\\?	?	<code>see("\\?")</code>
\\\\	\\	\\	<code>see("\\\\")</code>
\\(\\((<code>see("\\(")</code>
\\)	\\))	<code>see("\\)")</code>
\\{	\\{	{	<code>see("\\{")</code>
\\}	\\}	}	<code>see("\\}")</code>
\\n	\\n	new line (return)	<code>see("\\n")</code>
\\t	\\t	tab	<code>see("\\t")</code>
\\s	\\s	any whitespace (S for <i>non-whitespaces</i>)	<code>see("\\s")</code>
\\d	\\d	any digit (D for <i>non-digits</i>)	<code>see("\\d")</code>
\\w	\\w	any word character (W for <i>non-word chars</i>)	<code>see("\\w")</code>
\\b	\\b	word boundaries	<code>see("\\b")</code>
	[:digit:] ¹	digits	<code>see("[:digit:]")</code>
	[:alpha:] ¹	letters	<code>see("[:alpha:]")</code>
	[:lower:] ¹	lowercase letters	<code>see("[:lower:]")</code>
	[:upper:] ¹	uppercase letters	<code>see("[:upper:]")</code>
	[:alnum:] ¹	letters and numbers	<code>see("[:alnum:]")</code>
	[:punct:] ¹	punctuation	<code>see("[:punct:]")</code>
	[:graph:] ¹	letters, numbers, and punctuation	<code>see("[:graph:]")</code>
	[:space:] ¹	space characters (i.e. \\s)	<code>see("[:space:]")</code>
	[:blank:] ¹	space and tab (but not new line)	<code>see("[:blank:]")</code>
	.	every character except a new line	<code>see(".")</code>

¹ Many base R functions require classes to be wrapped in a second set of [], e.g. `[:digit:]`

[:space:]
← new line
space
tab

[:blank:]
space
tab

[:graph:]

[:punct:]
.,:;?!\\|/`=*+-^
_~" '[] { } () < > @ # \$

[:alnum:]

[:digit:]
0 1 2 3 4 5 6 7 8 9

[:alpha:]

[:lower:]	[:upper:]
a	A
b	B
c	C
d	D
e	E
f	F
g	G
h	H
i	I
j	J
k	K
l	L
m	M
n	N
o	O
p	P
q	Q
r	R
s	S
t	T
u	U
v	V
w	W
x	X
z	Z

ALTERNATES

```
alt <- function(rx) str_view_all("abcde", rx)
```

regex	matches	example
<code>ab d</code>	or	<code>alt("ab d")</code>
<code>[abe]</code>	one of	<code>alt("[abe]")</code>
<code>^[abe]</code>	anything but	<code>alt("^[abe]")</code>
<code>[a-c]</code>	range	<code>alt("[a-c]")</code>

ANCHORS

```
anchor <- function(rx) str_view_all("aaa", rx)
```

regex	matches	example
<code>^a</code>	start of string	<code>anchor("^a")</code>
<code>a\$</code>	end of string	<code>anchor("a\$")</code>

LOOK AROUNDS

```
look <- function(rx) str_view_all("bacad", rx)
```

regex	matches	example
<code>a(=?c)</code>	followed by	<code>look("a(=?c)")</code>
<code>a(?!c)</code>	not followed by	<code>look("a(?!c)")</code>
<code>(?<=b)a</code>	preceded by	<code>look("(?<=b)a")</code>
<code>(?<!b)a</code>	not preceded by	<code>look("(?<!b)a")</code>

QUANTIFIERS

```
quant <- function(rx) str_view_all(".a.aa.aaa", rx)
```

regex	matches	example
<code>a?</code>	zero or one	<code>quant("a?")</code>
<code>a*</code>	zero or more	<code>quant("a*")</code>
<code>a+</code>	one or more	<code>quant("a+")</code>
<code>a{n}</code>	exactly n	<code>quant("a{2}")</code>
<code>a{n,}</code>	n or more	<code>quant("a{2,}")</code>
<code>a{n,m}</code>	between n and m	<code>quant("a{2,4}")</code>

GROUPS

```
ref <- function(rx) str_view_all("abbaab", rx)
```

Use parentheses to set precedence (order of evaluation) and create groups

regex	matches	example
<code>(ab c)e</code>	sets precedence	<code>alt("(ab c)e")</code>

Use an escaped number to refer to and duplicate parentheses groups that occur earlier in a pattern. Refer to each group by its order of appearance

string (type this)	regex (to mean this)	matches (which matches this)	example (the result is the same as ref("abba"))
<code>\\1</code>	<code>\\1 (etc.)</code>	first () group, etc.	<code>ref("(a)(b)\\2\\1")</code>

